



#1600
DYOSEAL 100% ACRYLIC
BRUSH-ON
CAULK & SEALANT

PRODUCT DESCRIPTION

#1600 DYOSEAL is a quality 100% acrylic exterior brush on caulk. #1600 can take the beating of extreme weather conditions and it bonds tightly to clean and firm substrates. It forms a permanently flexible seal that will not crack, chip, or peel. It applies easily, dries rapidly and may be painted over after thoroughly drying.

RECOMMENDED USES

SURFACES: Masonry, asbestos, wood, asphaltic surfaces, flexible foams and metals (including aluminum and galvanized metal roofs).

PRODUCT ADVANTAGES

- ! Stays pliable
- ! Excellent elongation
- ! Excellent adhesion
- ! Excellent tensile strength
- ! Excellent on wood, metal and concrete
- ! Water clean up
- ! Resists mildew and sulfide staining, and ultra violet rays

MATERIAL PREPARATION

MIXING: Stir from bottom with vigorous strokes. Do not add oil or other paints.

LIMITATIONS

CAUTION: Allow one to two hours drying time, depending on atmospheric conditions. Do not apply when temperature is below 45 F., and protect from freezing. #1600 is not suitable for application where the cured bead will be submerged or subjected to frequent standing water. Keep from freezing.

SURFACE PREPARATION

Surface preparation is simple, consisting of proving a clean dry surface to ensure maximum results. Rust and grease should be removed with a wire brush, steel wool or industrial abrasive paper. On old paint surfaces remove loosed paint and chalking by scraping, wire brushing or industrial cleaner.

APPLICATION

DYCO #1600 may be applied by brushing, rolling, or troweling.

TECHNICAL DATA

Product Number - #1600

Generic Type - 100% Acrylic Latex

Color - White

% Solids by Weight - 80.42%

% Solids by Volume - 68.77%

% Vehicle Solids by Weight - 23.76%

% Pigment by Weight - 56.66%

% Volatile by Weight - 19.58%

Viscosity - Buttery

Weight/Gallon - 13.45 lbs

Dry Time - 70°F., 50% R.H.
1 - 2 hours

VOC - 52 G/L, (0.43 lbs/gal)

Clean Up Solvent- Water

LIMITATION OF LIABILITY

Technical data is true and accurate at date of issuance, but subject to change without notice. Our products conform to **DYCO** quality standards, but no other warranty or guarantee is expressed or implied. Liability, if any, is limited to replacement of product or purchase price. Labor, cost of labor, or other consequential damages is hereby excluded.