



#1605
DYOSEAL SILICONIZED
ACRYLIC 11 OZ. TUBE CAULK

PRODUCT DESCRIPTION

#1605 DYOSEAL is a quality 100% acrylic latex siliconized caulk. It can take the beating of extreme weather conditions and bonds tightly to any clean and firm substrates.

RECOMMENDED USES

SURFACES: Wood, aluminum, galvanized, concrete, masonry, glass, and ceramic tile.

PRODUCT ADVANTAGES

- * Easy to apply
- * Non-staining
- * Odor free
- * When cured remains flexible and water resistant indefinitely
- * Paintable after drying

LIMITATIONS

CAUTION: DO NOT apply when temperature is below 40° F. Keep from freezing.

SURFACE PREPARATION

Area to be caulked should be dry, clean, and free of dirt, dust, grease, or oil and any other surface contaminants.

LIMITATION OF LIABILITY

Technical data is true and accurate at date of issuance, but subject to change without notice. Our products conform to **DYCO** quality standards, but no other warranty or guarantee is expressed or implied. Liability, if any, is limited to replacement of product or purchase price. Labor, cost of labor, or other consequential damages is hereby excluded.

TECHNICAL DATA

Product Number - #1605

Generic Type- 100% Acrylic Latex
Color - White

% Solids by weight - 81.8%
% Solids by Volume - 72.9%

Recommended Coverage:
Approximately 20 linear ft. of
1/4" bead per 11 fluid oz.

% Vehicle Solids by Weight -
62.5%
% Pigment by Weight - 51.5%
% Solvent by Weight - 15.6%

Weight/Gallon - 13.01
Flash Point - None

Dry Time - 70° F., 50% R.H.
Touch - 20-40 minutes
Recoat - 1-2 hours

Clean Up Solvent- Water

Slump(inches)Channel Method - 0
Shore A Hardness - 64

Flexibility-Flexible below 0 F.
Elongation - 800-900 %

Dry Peel Adhesion-180 on
Glass-13 lb./in.
Wet Peel Adhesion-180 on
Glass-11lb./in.

Tensile Strength (psi) – 24



