



#20/20
CAULK/SEALANT
11 oz. TUBE

PRODUCT DESCRIPTION

#20/20 Tube Caulk is a premium flexible, elastic rubber copolymer caulk and sealant. It has excellent adhesion to variety of surface and dries exceptionally fast.

RECOMMENDED USES

SURFACES: Glass fiberglass, aluminum, wood, metals, and masonry.

HOME USES: Metal buildings, utility sheds mobile homes, windows, doors, siding, vents, seams, gutter, downspouts, awing, carports, screened porches, fascia, air conditioning, skylights, tubs, and showers.

TRANSPORTATION USES: RV vehicles, vans, buses, and trucks.

MARINE USES: Boats, hatches, windows, and above water line.

PRODUCT ADVANTAGES

- *Fast drying
- *Non-yellowing
- *Long lasting
- *Paintable after 24 hours
- *Excellent Weather ability
- *Remains pliable

LIMITATIONS

CAUTION: 20/20 may be applied in temperatures 40-120° F. And in all types of weather conditions, but the surfaces must be clean and dry. Any tooling should be completed within one minute after application.

SURFACE PREPARATION

Surface must be clean, dry, and free of dust, dirt, grease, oil and loose caulk or foreign material.

COLORS:

Clear, White & Ivory

LIMITATION OF LIABILITY

Technical data is true and accurate at date of issuance, but subject to change without notice. Our products conform to DYCO quality standards, but no other warranty or guarantee is expressed or implied. Liability, cost of labor or other consequential damages is hereby excluded.

TECHNICAL DATA

Product # 20/20 Caulk/Sealant

Generic Type-Rubber Copolymer

- % Solids by Wt. - 59.1%
- % Solids by Vol. - 51.2%
- % Vehicle Solids by Wt. - 56.3%
- % Pigment by Wt. - 6.6%
- % Solvent by Wt. - 40.9%

Wt. /Gallon - 7.71

Recommended Coverage:

Approx. 20 linear ft of 1/4" bead per 11 fluid oz.

Flash Point - 60° F.

Dry Time - 70° F., 50% R.H

Touch - 45-60 minutes

Recoat - 8-24 hours

Clean Up Solvent - Mineral Spirits

Slump(inches) Channel Method-0

Flexibility-Flexible below 0° F.

Elongation - 300-400%

Dry Peel Adhesion-

180 on Glass-40 pli

Wet Peel Adhesion -

180 on Glass - 40 pli

