



#3000
FIRST SEAL
WATER-BASE
WATERPROOFING
SEALER

PRODUCT DESCRIPTION

3000 First Seal is an Acrylic Waterborne Sealer that is specially formulated for stucco, masonry, and concrete surfaces. It may also be used on concrete block, plaster, drywall, brick, simulated brick, adobe, lightly chalked surfaces, (masonry and wood) roof tiles, asphalt shingles, and pottery. The product seals and waterproofs, dries clear, has low VOC and the ability to be painted.

RECOMMENDED USES

For waterproofing, sealing and preservation of stucco, concrete, masonry, and adobe. To lock down lightly chalked surfaces, allowing them to be painted. Aids in the prevention of efflorescence, erosion, moisture, chalking, spalling, cracking, mildew and other damaging effects due to water penetration. For dust proofing bare concrete.

PRODUCT ADVANTAGES

Environmentally safe, will not harm humans, animals, or vegetation. Non-toxic. Contains low volatile organic compounds (VOC=s). Non-flammable. Water based, requires no solvents, and is easy to clean up with water. First Seal goes on milky white and dries clear. It is fast drying and can be recoated when completely dry (approximately 1 to 3 hours). Offers waterproofing, sealing, and a binding action, which may be painted with acrylic/latex or oil, base paints. First Seal is mildew resistant.

LIMITATIONS

Do not apply to painted driveways and garage floors. Do not use as a top coat over stained or painted floors. Do not freeze. Do not apply to glazed tile. Do not apply over un-cured latex paint. First Seal will not stop hydrostatic pressure below grade. Do not apply to new brick or bare wood surfaces.

MATERIAL PREPARATION: DO NOT THIN. Stir before using.

SURFACE PREPARATION

Clean surface to remove dirt, grease or oils, foreign material and efflorescence. If used as a sealer over painted surfaces, remove all loose, peeling paint and excessive chalk and mildew. It is best to repair patch and fill cracks prior to applying First Seal. Always remember for proper application First Seal requires a clean and dry surface.

APPLICATION

Apply with hand pump sprayer or low-pressure airless sprayer. Roller or brush may be used, always strive for an even saturated coat of First Seal. Two coats are recommended. On asphalt shingles: 1-1 mix with water & apply two coats to lock in shingle granules.

LIMITATIONS OF LIABILITY

Technical data is true and accurate at date of issuance, but subject to change without notice. Our products conform to DYCO quality standards, but no other warranty or guarantee is expressed or implied. Liability, if any, is limited to re-placement of product or purchase price. Labor, cost of labor or other consequential damages is hereby excluded.

TECHNICAL DATA

Product Number - 3000

Generic Type-Acrylic Waterborne Sealer

Color - Clear

% Solids by Weight - 15.05%

% Solids by Volume - 14.45%

Recommended Coverage:
1 mil dry (calculated)
Avg. 250 sq ft per gallon

% Vehicle Solids by Wt.-15.05%

% Volatile by Weight - 84.95%

Maximum VOC - 400 grams/liter

Weight/Gallon - 8.45 lbs

Flash Point - None

Dry Time
Touch - 30 minutes
Recoat - 2 hour

Clean Up Solvent - Water

