



**#450**  
EZ SPREAD  
INT/EXT VINYL  
ACRYLIC WALL PAINT

### PRODUCT DESCRIPTION

A vinyl acrylic formulated in a flat sheen to provide good uniformity, hiding power and durability.

### RECOMMENDED USES

Interior/exterior wall paint for masonry, wallboard, plaster, stucco, concrete brick, and cement asbestos siding.

### PRODUCT ADVANTAGES

\* Outstanding uniformity and touch up \* Mildew resistant \* Easy to apply  
\* High Hiding \* Quick drying \* Clean up with soap and water

### MATERIAL PREPARATION

Mix thoroughly before using, stirring with a lifting motion. #450 series can be applied unthinned; however, thinning 2 pint per gallon is permissible.

### LIMITATIONS

DO NOT apply when temperatures of air or surface is below 50 E F., or when rain or inclement weather is threatening.

### SURFACE PREPARATION - SURFACE PROBLEMS

**Mildew** - Treat with a mildew remover, rinse thoroughly, let dry before painting.  
**Efflorescence** - (whitish deposit on masonry surfaces) treat with solution of 3 parts water to 1 part muriatic acid. Let sit 15 minutes then rinse before painting.  
**Chalk** Remove by hand scrubbing or pressure cleaning. Apply a chalk bonding primer; allow drying thoroughly then applying paint.

### SURFACE PREPARATION - SURFACE TO BE REPAINTED

The surface to be repainted must be free of any loose paint, grease, dirt, rust or other adherent surface contaminants. Cleaning may be accomplished by using a detergent solution, scraping, or wire brushing. The method of cleaning is based on the surface and substance being removed. Any glossy surface must be dulled by lightly sanding or use of a solvent etch.

### APPLICATION

Brush, roller, or spray

### PRIMERS

**Chalky Surfaces** - Use **DYCO #1315** Sure Prep. **Masonry** (porous unpainted) - Use **DYCO #990** Block filler.

### LIMITATION OF LIABILITY

Technical data is true and accurate at date of issuance, but subject to change without notice. Our products conform to DYCO quality standards, but no other warranty or guarantee is expressed or implied. Liability, if any, is limited to replacement of product or purchase price. Labor, cost of labor or other consequential damages is hereby excluded.

### TECHNICAL DATA

Product Number - #450

Generic Type - Vinyl Acrylic Latex

Color - White  
Sheen - Flat

% Solids by Weight - 48.84%  
% Solids by Volume - 33.05%

Recommended Coverage:

4.0 mils wet  
1.4 mils dry  
Avg. 200 to 400 sq ft per gallon

Vehicle Solids by Weight - 13.71%

Pigment by Weight - 35.14%

Solvent by Weight - 51.16%

PVC - 52.05%

Viscosity (Stormed) - 98-100 KU

Weight/Gallon - 10.96

Flash Point - None

Dry Time - 70E F., 50% R. H.  
Touch - 30 minutes  
Re-coat - 1 hour

Reduction Solvent - Water

Clean Up Solvent - Water

Tinting - Color trend Que System

450 - White/Pastel  
451 - Tint Base  
452 - Deep Base  
453 - Ultra Deep Base

