



#670
EZ SPREAD
EXTERIOR 100% ACRYLIC
SEMI-GLOSS

PRODUCT DESCRIPTION

A 100% acrylic, semi-gloss finish that provides quality protection with excellent uniformity and touch up qualities.

RECOMMENDED USES

#670 Semi-gloss exterior 100% acrylic paint may be applied to masonry, stucco, cement, drywall, asbestos siding, and primed wood.

PRODUCT ADVANTAGES

- * Outstanding sheen uniformity & touch up
- * Easy to apply
- * Quick drying
- * Clean up with soap and water
- * Mildew resistant
- * Non-sulfide staining
- * High hiding

MATERIAL PREPARATION

Mix thoroughly before using, stirring with a lifting motion. #670 series can be applied unthinned however, thinning with 2 pint per gallon is permissible.

LIMITATIONS

DO NOT apply when temperatures of air or surface is below 50° F., or when rain or inclement weather is threatening.

SURFACE PREPARATION - SURFACE PROBLEMS

Mildew - Treat with a mildew remover, rinse thoroughly, let dry before painting.
Efflorescence-(whitish deposit on masonry surfaces) treat with solution of 3 parts water to 1 part muriatic acid. Let sit 15 minutes then rinse before painting. **Chalk**-Remove by hand scrubbing or pressure cleaning. Apply a chalk bonding primer, allow to dry thoroughly then apply paint.

SURFACE PREPARATION - SURFACE TO BE REPAINTED

Remove loose or scaling paint, lightly sand, and spot prime. Glossy paint should be dulled by sanding or chemical treatment.

APPLICATION

Brush, roller, or spray.

PRIMERS

Chalky Surfaces - Use **DYCO #1315** Sure Prep. **Masonry** (porous unpainted) - Use **DYCO #990** Block filler (or a comparable primer). **Metal** - Use **DYCO #MP-50** Metal Primer. **Wood** - Unpainted - Use **DYCO #1410** Wood Primer or **#60-05** Water-base primer (or use comparable primers).

LIMITATION OF LIABILITY

Technical data is true and accurate at date of issuance, but subject to change without notice. Our products conform to **DYCO** quality standards, but no other warranty or guarantee is expressed or implied. Liability, if any, is limited to replacement of product or purchase price. Labor, cost of labor, or other consequential damages is hereby excluded.

TECHNICAL DATA

- Product Number - #670
- Generic Type - 100% Acrylic Latex
- Color - White
- Sheen - Semi-Gloss
- % Solids by Weight - 44.75%
- % Solids by Volume - 32.75%
- Recommended Coverage:
 4.0 mils wet
 1.6 mils dry
 Avg 200-400 sq ft per gallon
- % Vehicle Solids by Weight - 21.54%
- % Pigment by Weight - 23.21%
- % Solvent by Weight - 55.25%
- PVC - 25.50%
- Viscosity (Stormer) - 98-100 KU
- Weight/Gallon - 10.32 lbs.
- Flash Point - None
- Dry Time - 70° F., 50% R. H.
 Touch - 30 minutes
 Recoat - 1 hour
- Reduction Solvent - Water
- Clean Up Solvent - Water
- Tinting - Color trend Que System
 670 - White/Pastel
 671 - Tint Base
 672 - Deep Base
 673 - Ultra Deep Base
 675 - Neutral