



#7200
Clear Paver Sealer

PRODUCT DESCRIPTION

Dyco #7200 Cement Paver Sealer is a solvent acrylic, non-yellowing "clear" sealer for sealing non-sealed or coated pavers. Paver Sealer gives a wet-look and enhances the true color of the paver. How to determine if your pavers have been sealed with a latex water base sealer: Test the surfaces by pouring a small amount of water on the surface. If it penetrates quickly, the surface is porous and ready for #7200 Paver Sealer. If it does NOT and takes 2-20 minutes to penetrate, then DO NOT apply #7200 Paver Sealer.

RECOMMENDED USES

Concrete Cement Pavers

PRODUCT ADVANTAGES

- * Resists Tire Marking
- * Resists Cracking & Peeling
- * Resists Mildew
- * Easy To Apply

MATERIAL PREPARATION

MIXING: Stir from bottom with vigorous strokes. Do not add oil or other paints.

LIMITATIONS

CAUTION: DO NOT apply in temperatures below 50° F to a damp surface. On excessively hot surfaces, for example direct sunlight on a hot day, drying may occur too rapidly, causing trapped vapors to bubble. If this occurs, we recommend application during a cooler time of day. Keep away from children. Keep away from direct heat and open flame. This product is not recommended for wood or Bominite surfaces. Keep away from children. Keep away from direct heat and open flame.

SURFACE PREPARATION

On bare pavers, the surface must be clean, dry, and free of all grease, oil, and dirt. If necessary, clean with a good degreaser and brush, and/or pressure wash for best results. Surface will be tack free in 1 hour, ready for foot traffic in 2 hours and vehicle traffic in 72 hours. On bare concrete, the surface must be clean and dry.

APPLICATION

Brush, roll, or spray. When applying use a short nap solvent resistant roller cover (3/8" Nap). Apply evenly, and do not leave puddles or roller marks. Dip roller cover into the Paver Sealer and roll forward allowing wet sealer in front of the roller to penetrate the deeper crevices around the paver. Do not dry roll, keep plenty of sealer on roller cover. Only one coat is recommended. Do not apply to areas where standing water is evident. Where there is a possibility of slipperiness, DO NOT APPLY THIS PRODUCT. If there has been a skid-texture added to the sealer, this product may perform properly but all precautions must be taken. Recommended coverage is 100-125 sq. ft. per gallon. Clean tools and equipment with Xylene solvent.

DANGER! EXTREMELY FLAMMABLE B CONTAINS XYLENE

Keep away from heat, sparks, and flame. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air or wear respiratory protection (MOSH/MSHA TC23C or equivalent) or leave the area. Close container after each use. Avoid contact with skin.

TECHNICAL DATA

Product Number B 7200
Generic Type B Solvent Acrylic

Color - Clear
Sheen B Gloss

% Solids by Weight B 25.84%
% Solids by Volume B 21.56%

Recommended Coverage:
Avg 100-125 sq ft per gal
on porous surfaces

% Vehicle Solids by Weight B 25.84%
% Solvent by Weight B 74.15%

Viscosity #2 Zahn - 19 Sec.
Maximum VOC B 683.30 Grams/Liter
(5.70LB/GL)

Weight/Gallon B 7.68 LBS

Flash Point - 81°F.

Dry Time - 70° F., 50% R. H.
Touch - 1 hour (depending on
weather) Recoat - 2 hours

Reduction Solvent B Do Not Thin
Clean Up Solvent - Xylene

LIMITATION OF LIABILITY

Technical data is true and accurate at date of issuance, but subject to change without notice. Our products conform to DYCO quality standards, but no other warranty or guarantee is expressed or implied. Liability, if any, is limited to replacement of product or purchase price. Labor, cost of labor, or other consequential damages are hereby excluded.

