



WB40 Series
Dock N Deck
Stain Sealer

PRODUCT DESCRIPTION

DYCO #WB SERIES DOCK & DECK STAIN SEALER is an advanced state-of-the-art acrylic waterborne finish. **WB Series** Dock & Deck Stain Sealer is a penetrating stain & sealer to protect exterior wood surfaces such as docks, deck, and fences. Fortified with transoxide pigment.

SURFACE PREPARATION

Dirt, grease, grime and any foreign material must be removed before applying Dock & Deck Stain Sealer. **DYCO #WB Series** Dock & Deck Stain Sealer resists moisture penetration and retards the aging process of new wood. **DYCO #WB** Dock & Deck Stain Sealer resists mildew and is fortified with UV protection to guard against the harsh sunrays.

DO NOT use on previously painted or varnished wood surfaces. All rotten and deteriorated wood must be replaced as well as broken or corroded hardware. Remove all grease, dirt, mildew, and algae with **DYCO WC59** Weathered Wood Cleaner and Brightener as per label directions. A comparable wood cleaner and brightener is acceptable.

Mill glazed and pressure treated lumber should be allowed to weather slightly to allow proper penetration of the stain. Other wood may be stained at any time before heavy graying starts. Smooth, new wood should be sanded with 50-80 grit sandpaper to remove mill glaze and ensure proper penetration and adhesion.

APPLICATION

Stir vigorously from the bottom of the can to ensure thorough mixing before application. Apply liberally using a paintbrush, roller, or spray equipment. If the dock or deck surface is hot and dry, apply clean water to cool the surface and apply Dock & Deck Stain Sealer to a cool, moist surface.

On Check or cracked wood surfaces, apply the stain liberally to penetrate the cracks. Avoid runs and puddles, and when applying by paintbrush or roller, avoid lapping. Work with a wet edge and always apply with the grain of the wood. Stop at a logical break point to avoid creating lap marks. Two even coats are recommended. The second coat may be applied as soon as the first coat is completely dry to the touch, usually 2 to 4 hours.

LIMITATION OF LIABILITY

Technical data is true and accurate at date of issuance, but subject to change without notice. Our products conform to **DYCO** quality standards, but no other warranty or guarantee is expressed or implied. Liability, if any, is limited to replacement of product or purchase price. Labor, cost of labor or other consequential damages is hereby excluded.

TECHNICAL DATA

Product Number - WB Series

Generic Type - Waterborne
Sheen - Satin

% Solids by Weight - 22.01%
% Solids by Volume - 20.77%

Recommended Coverage:

3.0 mils wet

1.0 mils dry

Avg. 200-400 Sq. Ft. per gallon
depending on porosity & texture
of wood.

% Vehicle Solids by Wt - 21.09%
% Volatile by Weight - 77.99%

PVC - 1.37%

Weight/Gallon - 8.59 lbs.

Maximum VOC - 400 grams/liter

Flash Point - None

Dry Time - 70° F., 50% R.H.

Touch - 45 minutes

Recoat - 4-6 hours

Clean Up Solvent - Water

Colors - WB 40 Natural
WB 41 Weathered Grey
WB 42 Redwood
WB 43 Navajo

